## PHP9030DT GE Profile<sup>™</sup> 30" Built-In Touch-Control Induction Cooktop

of air intake

1-3/4" MIN

to rear wall

## DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)

**IMPORTANT**: Requires a 3" free area between the bottom of the cooktop to any combustible material, i.e., shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Requires a 15" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.

**NOTE:** 30" induction cooktops are approved for use over select GE 27" and GE 30" Single Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current dimensional data. If installed with a GE Telescopic Downdraft System, consult both the cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft. The countertop cutout requires 23-1/2" minimum flat countertop surface and 25" minimum total countertop depth. In addition, other clearances to front edge of the countertop must be considered. Before installing, consult installation instructions packed with product for current dimensional data.

**CUTOUT FILLER TRIM KIT:** A filler trim kit is available for use if your countertop cutout is larger than the dimension shown, up to 29-13/16''x 20-7/16". Order JXTR32B for black or JXTR32W for white, to reduce the cutout opening for installation of this cooktop. These kits may be ordered from your GE Appliances Dealer.



## INSTALLATION ABOVE A WALL OVEN



KW RATING	
240V	7.4
208V	6.4
AMPERAGE	
240V	40 Amps <sup>+</sup>
208V	40 Amps <sup>+</sup>

\*NOTE: Check local codes for required breaker size





For answers to your Monogram, GE Café<sup>™</sup>, GE Profile<sup>™</sup> or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center<sup>®</sup> Service, 800,626,2000.

# **PHP9030DT** GE Profile<sup>™</sup> 30" Built-In Touch-Control Induction Cooktop

## FEATURES AND BENEFITS

Maximum Responsiveness - 19 Control Levels Power Boil Precision Temperature Control Guided Cooking Easy Clean Surface Safe Surface Most Efficient Heating Synchronized Elements Chef Connect Smart Cookware Rebate for 11" Smart Pan Timer Built-in WiFi Control Lock Fit Guarantee Model PHP9030DTBB – Black on black



#### SMART COOKWARE REBATE

Smart pans pair with this smart cooktop to ensure you get the perfect cooking results. Earn a rebate for a free 11" Hestan Cue Smart Pan.

### **OPTIONAL FILLER TRIM KIT**

Fill in any counter top gaps with this filler trim kit. Order part number JXTR32B.

### **OPTIONAL SOUS VIDE PROBE**

A Sous Vide Probe lets you achieve great results on the stove. Order part number JXPROBE1.

### **GUARANTEED FIT**

Replacing a similar cooktop from GE Appliances or another brand? GE cooktops are guaranteed for an exact fit or GE Appliances will pay up to \$100 toward modifications.

Visit geappliances.com for more info.

