







Product: 30 Inch Professional Dual Fuel Range in Stainless Steel **Model Number:** HRD3088U / HRD3088ULP

TECHNICAL DETAILS		
Fuel Type	Natural Gas / LP Convertible	
Electrical Requirements	240V, 4-Prong 14-50R Power Outlet	
Circuit Breaker (A)	30A	
Frequency (Hz)	60 Hz	

BURNER PERFORMANCE		
Total Burners	4	
[1] Front Left (Single)	18,000 BTU	
[2] Front Right (Dual Burner with simmer function)	15,000 BTU (650 BTU for Simmer)	
[3] Rear Left (Single)	12,000 BTU	
[4] Rear Right (Single)	12,000 BTU	



FEATURES & BENEFITS

- High-Powered BTU Burners From a high-powered 18,000 BTU burner to a burner with a steady 650 BTU simmer function, this range gives you the power you need for large family meals and the consistent low heat desired for cooking delicate sauces or melting chocolate
- Energy Efficient Heating Heating element distributes heat evenly for excellent broiling and baking
- + Commercial Convection Fan Convection fan provides controlled heat distribution for fast and efficient cooking
- LED Control Panel Lights When in operation, the LED control panel lights illuminate a striking blue for an added pop of color
- → Large Oven Capacity 4.2 cu. ft. oven capacity can accommodate
 multiple dishes for enhanced cooking
- Continuous Cast-Iron Cooking Grates Heavy-duty continuous cast-iron cooking grates that can handle any size cookware
- + Brilliant Blue Porcelain Interior The brilliant blue porcelain interior adds a bold, stylish touch to your professional range
- + Heavy Duty Control Knobs Heavy duty, die-cast metal burner control knobs add style and durability
- Black Porcelain Spill Tray Black porcelain spill tray on cooktop catches the mess and makes cleanup easy
- Automatic Reignition Feature Automatic reignition feature relights an extinguished flame for safer cooking

OVEN PERFORMANCE		
Oven Capacity	4.2 cu. ft	
Bake Power	850 W top 3000 W bottom	
Broil Power	3,500 W	

WARRANTY: 2 YEARS ON PARTS AND LABOR








30 INCH DUAL FUEL RANGE HRD3088U / HRD3088ULP


PRODUCT DIMENSIONS			
Product Width	30"		
Product height (from bottom to top of back splash)	38 1/2"-39 1/2"		
Product height (from bottom to top of side panel)	35 15/16"- 36 15/16"		
Product depth (from back panel to bullnose)	27 7/8"		
Product depth (from back panel to control board)	26 1/2"		
Product depth (from back panel to side panel front)	24 3/16"		
Depth of control panel (minimum)	2 1/4"		
Depth of control panel (bullnose)	3 11/16"		
Cast iron cooking grate (W x L)	10 3/4" x 23"		
Adjustable Legs	Not to Exceed 1"		

REQUIRED CUTOUT SIZE 30 1/8" x 24 13/16" x 35 15/16" (+1")

OVEN DIMENSIONS		
Oven Cavity Dimension	24"W x 15 1/4"H x 18"D	
Oven Rack Dimension	22 3/4" x 15 1/2"	
Distance Between Oven Rack	2 1/8"	

ACCESSORIES (NOT INCLUDED)		
Liquid Propane Gas Conversion Kit	LPKHRD3088U	
30-inch Telescopic Rack	TR30SS	
Wok Ring	WK01	
30-inch Island Trim	ITHRD3088U	
Cast Iron Reversible Griddle	RG1022	





HRD3088U

NG: Input Pressure: 7 inches, Output Pressure: 5 inches LP: Input Pressure: 11 inches Output Pressure: 10 inches Regulator Location: Inside the kick Panel – Bottom Right Size of Regulator: ½ inch

